

## CTX609\_V.3 V.92 PCI Modem

### Product Specification

**FEATURES:**

- PCI Version 2.2 compliant
- Up to 56kbps V.92 data rate\*
- Support operating systems such as Windows 2000/XP, Vista
- PCI Softmodem

**MODEM Standard**

- V.92 (down-stream) up to 56,000 bps\*;
- V.34bis (up to 33,600 bps)
- V.34 (2,400 to 28,800 bps)
- V.32bis, V.32, V.22bis, V.22/Bell 212A, V.21/Bell 103

**FAX Standard**

- Group 3, class 1
- EIA Class fax commands
- V.17 (14,4K bps), V.29 (9,6K bps), V.27ter (4.8K bps),
- V.21 (300bps), ITU-T T.31 Class 1 FAX

**Approvals:**

- EN55022, EN55024, EN60950, TS103021
- RoHS-conform

**Supply voltage:**

- 3.3V / 50mA

**Power dissipation:**

- ~165mW

**Line Interface:**

- Europe

**PCB Revision:**

- CTX609V3 08232006

**Chipset:**

- Agere SV92PP
- Agere CSP1040

\*Due to power limitation in the telephone network data receiving is possible up to 54,3 kbps maximum only.

**ORDERCODE**

- CTX609\_V3 V.92 Modem